

CROSS

— S —
ORKAN 6 CSM



red
-white



graphite
-black



ORKAN 6 CSM

Technical data

WHEEL SIZE / FRAME	28" / alu 6061	RIMS	aluminium doublewall
SIZE	M – 18" / L – 20"	FRONT HUB	Shimano HB-TX505
FORK	Suntour NEX E-25 NLO 75mm tapered	REAR HUB	Shimano FH-TX505
DAMPER	—	CASSETTE	Shimano CS-LG400 11-39T, 10 speed
DRIVETRAIN	2×10	HANDLEBAR	RMT Comp. aluminium 680mm/31,8mm
FRONT SHIFTERS	Shimano Cues SL-U6000 2 speed	STEM	RMT Comp. adj. 85mm Internal cable routing
REAR SHIFTERS	Shimano Cues SL-U6000 10 speed	SEAT POST	RMT Components 27,2mm/350mm
FRONT DERAILLEUR	Shimano Cues FD-U6010	GRIPS	Wittkop Medicus Sport
REAR DERAILLEUR	Shimano Cues RD-U6020 SGS	SADDLE	Selle Royal Ariel 8058 HR
CRANKSET	Shimano Cues FC-U6000-2, 46-30T 170mm	PEDALS	FP-920B
FRONT BRAKE	Shimano BL-MT200/BR-M200	FRONT LAMP	—
REAR BRAKE	Shimano BL-MT200/BR-M200	REAR LAMP	—
FRONT BRAKE DISC	Shimano SM-RT10 centerlock 160mm	WEIGHT	15,6 kg
REAR BRAKE DISC	Shimano SM-RT10 centerlock 160mm	COLOURS	red-white, graphite-black
TYRES	VeeTire Speedster 700×44C		

Geometry

	M	L
Tyre size	28"	28"
A - frame size	510 mm	530 mm
B - top tube length	580 mm	585 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	68°	68°
E - head tube angle	71°	71°
F - wheel base	1083 mm	1083 mm
G - head tube length	135 mm	145 mm
H - fork length	450 mm	450 mm
Stack	604 mm	614 mm
Reach	401 mm	403 mm
Standover height	—	—
Maximum tyre size	1,75"	1,75"

