



E-RAMBLER 2.0

504Wh



blue
-silver



silver
-graphite



Bafang G020



250W 45Nm



504Wh



9 speed

E-RAMBLER 2.0_{504Wh}

Technical data

MOTOR / PERFORMANCE	Bafang G020 rear wheel, 250 Watt, 45Nm speed sensor	TYRES	Veetire Crown Gem 29"×2.30"
CONTROL UNIT	display Bafang DP C220 CAN	RIMS	aluminium doublewall RMT Components
BATTERY	504Wh	FRONT HUB	aluminium
CHARGER	2A	REAR HUB	—
WHEEL SIZE / FRAME	29" / alu 6061	CASSETTE	Shimano Cues CS-LG300-9, 11-41T, 9 speed
SIZE	M – 18" / L – 20"	HANDLEBAR	RMT Components aluminium 720mm, 31,8mm
FORK	SR Suntour XCM32-DS-LO, 100mm, tapered	STEM	RMT Comp. alu. 80mm/90mm Int.cable routing, 31,8mm
DAMPER	—	SEAT POST	RMT Components aluminium 30,9mm/350mm
DRIVETRAIN	1×9	GRIPS	Wittkop Medicus Sport
FRONT SHIFTERS	—	SADDLE	Romet
REAR SHIFTERS	Shimano Cues SL-U4010 9 speed	PEDALS	FP-803
FRONT DERAILLEUR	—	FRONT LAMP	—
REAR DERAILLEUR	Shimano Cues RD-U4000	REAR LAMP	—
CRANKSET	Prowheel 38T 170mm	WEIGHT	24 kg
FRONT BRAKE	Shimano BL-MT200 hydraulic	COLOURS	blue-silver, silver-graphite
REAR BRAKE	Shimano BL-MT200 hydraulic		
FRONT BRAKE DISC	180mm		
REAR BRAKE DISC	160mm		

Geometry

	M	L
Tyre size	29"	29"
A - frame size	457 mm	508 mm
B - top tube length	601 mm	625 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	73°	73°
E - head tube angle	70°	70°
F - wheel base	1116 mm	1140 mm
G - head tube length	140 mm	140 mm
H - fork length	517 mm	517 mm
Stack	671 mm	671 mm
Reach	396 mm	420 mm
Standover height	793 mm	822 mm
Maximum tyre size	2.30"	2.30"

